

# UnyPOS 15" TFT Active Matrix LCD Display



REAR VIEW



SIDE VIEW



## MAIN SPECIFICATIONS U09T190WUR-SB

LCD Panel	15" TFT Active Matrix LCD Display
Resolution	1024 x 768 Pixels, 16.7M Colors
Contrast Ratio	500:1
Brightness	250 cd/m <sup>2</sup>
Response Time	12 ms
Pixel Pitch	0.297 mm x 0.297 mm
Plug & Play	DDC 2B Compliance
OSD (On Screen Display)	Auto Tune, Brightness, Contrast, Clock, Phase, H-position, V-position, Recall
Touch Technology	5 Wire Resistive, Capacitive, IR, SAW Technology
Touch Interface	Dual (Serial/USB)
Touch Active Area (W/H)	11.95" (303.50mm) x 8.96" (227.50mm)
Operating Environment	0°C-40 °C (32 °F-104 °F) 10%-80% (no condensation)
Storage Conditions	-20 °C-60 °C (-4 °F-140 °F) 10%-90% (no condensation)
Product Dimensions (W/H/D) mm	13.5"(343mm) x 14.3"(363mm) x 7.3"(185mm)
Package Dimensions (W/H/D) mm	18.6"(472mm) x 17.5"(444mm) x 8.2"(208mm)
Weight Gross	15.8 Lbs (7.16 Kgs)
Stand Style	U-Mount Cable a Base
Mounting Option	Desktop Placement, Bolt Down & VESA Mountable
Monitor Tilting Degree	160°
Color	Black
Viewing Angle	-75°/+75°/-60°/+60°(L/R/U/D)
MTBF	50,000 Hours
PC Video Interface	Analog RGB (VGA)
Horizontal Scan Rate (Khz)	30-60 Khz
Vertical Scan Rate (Hz)	56-75 Hz
Display Mode	VGA 7z20 x 400 (70 Hz) VGA 640 x 480 (60/66/70/72/75 Hz) SVGA 800 x 600 (60/70/72/75 Hz) XGA 1024 x 768 (56/70/75 Hz)
Front Control	Power On/Off with LED, Menu Auto Tune, Adjustment (+/-)
Buil-in-Speaker	Yes
Electrical Power	Adapter Input 100-240 VAC, 50-60 Hz 1.5A Adapter Output 12VDC, 3.33A (C+)
Power Consumption	30W (Max)
Certification	FCC, CE, UL, TCO99, CB, SASO, FDA

Visit us:  
[www.unypos.com](http://www.unypos.com)  
[sales@unypos.com](mailto:sales@unypos.com)

### APPLICATIONS:

- Retail
- Hospitality
- Home & Office
- Medical & Education

## Unypos Manufacturing, Inc.

G6434 South Dort Highway  
 Suite 2 & 3  
 Grand Blanc, Michigan 48439  
 Office: 810-953-3901  
 Fax: 810-953-3913